



| Modèle actionneur | 0M0 | 014 | 014P | 024 | 034 | 054 | 074 | 084 | 094 | 124 | 144 | 154 | 164 | 184 | 214 | 304 |
|-------------------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| A (mm) | 32.0 | 72.0 | 73.5 | 93.0 | 113.0 | 132.0 | 178.0 | 208.0 | 227.0 | 294.0 | 357.0 | 433.0 | 525.0 | 680.0 | 842.0 | 680.0 |
| B (mm) | 30.7 | 59.2 | 60.0 | 76.0 | 91.4 | 114.0 | 146.0 | 167.0 | 187.0 | 239.0 | 306.0 | 353.0 | 425.0 | 554.0 | 660.0 | 554.0 |
| C (mm) | 12.5 | 14.0 | 14.0 | 24.1 | 28.0 | 33.6 | 43.4 | 46.3 | 54.7 | 68.0 | 84.0 | 101.0 | 125.0 | 162.0 | 189.0 | 162.0 |
| N (nombre) | 4 | 4 | 4 | 4 | 4 | 6 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 8 | 8 |
| T (ISO) | M3 | M4 | M4 | M4 | M5 | M5 | M8 | M8 | M10 | M12 | M16 | M16 | M24 | M30 | M30 | M30 |
| D (mm) | 5.0 | 6.0 | 6.0 | 8.0 | 10.0 | 10.0 | 16.0 | 16.0 | 20.0 | 24.0 | 28.6 | 28.5 | 38.0 | 50.0 | 50.0 | 50.0 |
| R (mm) | | | | 18.0 | 22.0 | | 36.0 | 49.5 | 46.0 | 55.0 | 69.9 | 99.0 | 108.0 | 160.0 | 160.0 | 160.0 |
| PCD (mm) | 16.0 | 19.0 | 19.0 | 25.5 | 31.1 | 34.9 | 50.8 | 70.0 | 65.0 | 77.8 | 98.8 | 140.0 | 152.7 | 226.3 | 226.3 | 226.3 |
| ØK (mm) | | 9.5 | 9.5 | 16.0 | 18.0 | 19.0 | 32.0 | 36.0 | 38.0 | 50.0 | 57.0 | 70.0 | 85.0 | 115.0 | 150.0 | 150.0 |
| L (mm) | | 12.7 | 12.7 | 20.0 | 22.0 | 25.4 | 40.0 | 42.0 | 50.0 | 56.0 | 63.5 | 80.0 | 90.0 | 130.0 | 170.0 | 170.0 |

| Modèle actionneur | 0M0 | 014 | 014P | 024 | 034 | 054 | 074 | 084 | 094 | 124 | 144 | 154 | 164 | 184 | 214 | 304 |
|-------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|
| □ G1 (mm) | | 4.8 | 4.8 | 8.0 | 9.0 | 9.5 | 16.0 | 17.0 | 19.0 | 25.0 | 28.6 | 36.0 | 41.0 | 57.0 | 73.0 | 73.0 |
| □ G2 (mm) | | 4.8 | 4.8 | 8.0 | 9.0 | 9.5 | 16.0 | 16.0 | 16.0 | 16.0 | 16.0 | 16.0 | 41.0 | 57.0 | 73.0 | 73.0 |
| H (mm) | 36.0 | 38.0 | 38.0 | 50.0 | 60.0 | 67.0 | 100 | 110.0 | 126.0 | 156.0 | 200.0 | 245.0 | 274.0 | 360.0 | 410.0 | 880.0 |
| ØF (mm) | | | | | 33.6 | | 64.0 | | 84.0 | 100.0 | 127.0 | 138.0 | 175.0 | 286.0 | 298.0 | 286.0 |
| S1 (mm) | 10.0 | 7.0 | 7.0 | 10.0 | 12.0 | 13.0 | 20.0 | 19.0 | 26.0 | 31.0 | 38.0 | 41.0 | 55.0 | 78.0 | 100.0 | 100.0 |
| S2 (mm) | 10.0 | 12.7 | 12.7 | 10.0 | 12.0 | 13.0 | 20.0 | 20.0 | 20.0 | 35.5 | 35.5 | 35.5 | 55.0 | 78.0 | 100.0 | 100.0 |
| S3 (mm) | 2.0 | 6.7 | 6.7 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 12.5 | 12.5 | 12.5 | 0.0 | 0.0 | 0.0 | 0.0 |
| P (ISO) | M5 | G1/8 | G1/8 | G1/8 | G1/8 | G1/8 | G1/4 | G1/4 | G1/4 | G3/8 | G1/2 | G1/2 | G1/2 | G1/2 | G1 | G1 |
| Masse (kg) | 0.12 | 0.28 | 0.35 | 0.44 | 0.70 | 0.78 | 1.80 | 2.54 | 3.86 | 6.90 | 13.40 | 21.00 | 37.40 | 71.40 | 177.00 | 273.00 |
| ATEX | | cat 1 | cat 1 | cat 1 | cat 1 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 | cat 2 |

Actionneur 103-100 : cf K115 (actionneurs ISO/DIN)